LIGHT-DUTY COMMERCIAL DOOR OPERATOR FOR ROLLING DOORS

WiFi BUILT IN

LIGHT-DUTY APPLICATIONS

ROLLING DOORS
Ideal for Applications Using Smaller, Lighter Commercial Doors with Light-Duty Cycle Requirements

WALL MOUNT
on Small Rolling Doors and Grilles

SMART

myQ® TECHNOLOGY ENABLES MONITORING AND CONTROL OF THE FACILITY OPERATORS THROUGH A MOBILE APP.

BUILT-IN WI-FI® FOR SIMPLE OPERATOR INTERNET CONNECTION.

REAL-TIME ALERTS INDICATE THE STATUS OF DOORS VIA EMAIL OR PUSH NOTIFICATIONS.

QUIET AND SECURE

SMOOTH START/STOP REDUCES WEAR FOR LASTING PERFORMANCE.

BATTERY BACKUP CAPABLE: ENSURES ACCESS EVEN WHEN THE POWER'S OUT.

SECURITY+ 2.0® SAFEGUARDS FACILITY ACCESS WITH ROLLING CODE TECHNOLOGY, OPENING FOR REGISTERED DEVICES ONLY.

THE PROTECTOR SYSTEM® AUTO-REVERSES THE DOOR IF AN ENTRAPMENT PROTECTION DEVICE DETECTS AN OBSTRUCTION.

UL® 325 REQUIRES ALL COMMERCIAL DOOR OPERATORS TO BE EITHER CONSTANT PRESSURE TO CLOSE OR BE EQUIPPED WITH A PRIMARY EXTERNAL MONITORED ENTRAPMENT DEVICE.

RELIABLE

WARRANTY 2 YEARS.

BEYOND INDUSTRY STANDARDS: LIFTMASTER® IS COMMITTED TO QUALITY PRODUCTS, INNOVATIVE DESIGN AND COMPREHENSIVE SERVICES.

OPTIONAL ACCESSORIES:

myQ REMOTE LED LIGHT — 827LM
Operates automatically with the operator and works with the myQ App.

BATTERY BACKUP CAPABLE — 485LM
Powers up the operator when the power's out.

CHAIN GUARD WITH MOUNTING CLIP — 3950CGJ
Required for applications where the LJ8950W is mounted less than 8 ft. from the floor.

DEAD SHAFT SPROCKET KIT — 3950-41DS
For door applications without a live shaft, such as self-storage, requiring heavier #41 chain in place of standard #48 chain.

MOUNTING BRACKET — 3950MB
Optional bracket provides additional mounting flexibility either outside or inside the door opening.

LIGHT CURTAIN — LC-36A
Provides 36 inches of increased zone coverage for additional protection; indoor use; requires separate power source (100MAPS); max. range: 33 ft.

POWERFUL ADD-ONS:

1-BUTTON REMOTE CONTROL — 811LM
Ideal for commercial applications requiring a large number of remotes for a common entrance.

WIRELESS KEYPADS — KPW5/KPW250
NEMA 4X (water protection requirements) sealed electronics for reliable outdoor use.

LiftMaster offers accessory solutions for any commercial application. View the full product lineup at LiftMaster.com

LiftMaster®

LJ8950W

LIGHT-DUTY
JACKSHAFT OPERATOR

MASTERFUL ENGINEERING.

MOTOR

- 12V DC
- Automatic Thermal Protection
- Permanent Lubrication
- Duty Cycle: Maximum 10 Cycles per Hour; Fewer than 25 Cycles per Day

POWER

- 120V AC
- 60 Hz Voltage
- 1.5A Current Rating
- UL® Listed
- 6' Power Cord (3-Prong)

COMMERCIAL-GRADE DESIGN

- **Steel Chassis and Rigid Plastic Cover**
- **Internal Chain and Sprocket Drive Mechanism** (63:1 Gear Reduction)
- **Auto-Force** Adjustment for Changing Weather and Environmental Conditions
- **Electronic Limits** for Easy Setup
- **DC Wi-Fi® Logic Board** with Built-In Surge Suppressor (for Replacement Logic Boards, Order Part 050DCJCWFRD)
- **Live and Dead Shaft Door Sprockets** Are Both Included for #48 Chain

STANDARD SPECS.

SECURITY+ 2.0®
RADIO CONTROLS
Operating Range: ~200'

Optional 1-Button Remote Control (811LM)
- Commercial Door Operator

MAXIMUM DOOR AREA (SQ. FT.)

	MAX. HEIGHT		MAX. WIDTH	MAX. SQ. FT.
ROLLING	12 FT.	OR	18 FT.	180 FT. TOTAL

HEADROOM CLEARANCE REQUIRED: 3 IN. FROM CENTER OF TORSION BAR
MAX. DOOR WEIGHT: 650 LBS. / 850 LBS.*
*BATTERY BACKUP REQUIRED

SHIPPING.

SHIPPING WEIGHT
(in lbs.)

32
CARTON

CARTONS (1)
CARTON 1: 28" x 10" x 12"
- Commercial Door Operator (LJ8950W)
- #48 Chain and Sprockets (Live and Dead Shaft)
- Push-Button Control Station (APBS1)
- The Protector System® Safety Reversing Sensors

LIGHT-DUTY APPLICATIONS.

The LJ8950W is for applications using smaller, lighter rolling commercial doors requiring 25 cycles or fewer per day. This operator is ideal for:

- **Dock doors**
- **Small warehouses**
- **Self-storage**
- **Counter shutters**

© 2022 The Chamberlain Group LLC. All Rights Reserved. LiftMaster, the LiftMaster logo, myQ® and the myQ® logo are registered trademarks of the Chamberlain Group LLC.
300 Windsor Drive, Oak Brook, IL 60523
LiftMaster.com
Wi-Fi® is a registered trademark of Wi-Fi Alliance
UL® and the UL logo are trademarks of UL LLC © 2022 All Rights Reserved.
LMCDENPG8950WMC21 1/22

LiftMaster®